

B8TURBOVZ5

2MP CMOS Motorized Vari-focal IR Bullet Camera

epcom®



► Key Features

2MP CMOS sensor

HD1080p video output

0.1Lux @ (F1.2,AGC ON), 0 Lux with IR

5-50mm motorized VF lens, auto focus

True Day/Night

OSD menu, 3D-DNR, slow shutter, SMART IR

Up the Coax(HIKVISION-C, Pelco-C protocol)Up the Coax

► Camera

Image Sensor 2.0Mega Progressive Scan CMOS

Signal System PAL/NTSC

Effective Pixels 1956(H)×1266(V)

Min. illumination 0.01Lux @ (F1.2,AGC ON),0 Lux with IR

Shutter Time 1/25(1/30)sec~ 1/50,000sec

Lens Mount 5-50mm motorized VF lens

Day & Night ICR

Angle Adjustment Pan: 0° - 360°; Tilt:0° - 90°; Rotate: 0° - 360°

Synchronization Internal Synchronization

WDR 120dB

Video Frame Rate 1080P@25/30fps

HD Video Output 1 turbo HD output

CVBS Output 1Vp-p Composite Output(75Ω/BNC)

S/N Ratio >62dB

► Menu

Camera ID On/off(15 characters, position programmable)

AGC Support

D/N Mode Color/BW/EXT

White Balance ATW/ AWC-SET/ Manual

Privacy Mask On/Off, maximum 8 zones

Motion Detection On/Off, maximum 4 zones

BLC Support

Anti-flicker On/off

Language Chinese/ English

White Balance Eclipse,Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM

Scene Indoor/ Outdoor/ Indoor1/ LOW-LIGHT

► General

Operating Conditions -40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)

Power Supply AC24V±15%/ DC12V±15%
Heater is available with 24VAC only

Power Consumption Max. 11W(heater off)
Max. 20W(heater on)

Protection Level IP67

IR Range 100-110 m

Communication CVBS output: Pelco-C(need UTC controller)

Dimensions 313.5*100.8*107.3

Weight Approx. 1700 g